

Non-woven Machinery

Popular machines

Machinery List

Folding machinery

Rewinding machinery

Wet Tissue Machine

Packing machinery

RPM-400

RPS-400

RPM-450

General machine

Hot Towel dispenser

Product Line

Nonwoven Product

Nonwoven Material

Service Center

Online order

About us

RIWAY NONWOVEN INDUSTRIAL CO.,LTD

[Home](#) > [Products](#) > [Packing Machine](#) >

[Far infrared hot shrink tunnel machine](#)

Far infrared hot shrink tunnel machine

Far infrared hot shrink tunnel machine is very widely used..It uses the contraction membrane to carry on the hot contraction packing to the goods. It not only may carry on the single unit packing ,causes the product directly to stock merchandise for sale, also may use for parts the assembly line work packing. Suit each kind of use situation, passes through it to pack after the product, not only has the good transparency, the outlook artistic neat, had guaranteed the bedding bag installs the good clean, has the good moisture-proof performance, simultaneously in transports and stores in the process to get up the certain cushioning effect, occupies the space to be smaller.

Far infrared hot shrink tunnel machine is one kind of new modernized ideal packing equipment. It enhanced the product packing scale, the economic efficiency and the spcial efficiency is good.



FAR INFRARED HOT SHRINK MACHINE



- may provide the relativity moisture-resistance, is especially more important in e the stack board packing.
- use the advanced heat insulation result and the thermal insulation material, the energy conservation provide electricity enhance the efficiency.
- transmission devices revolution steady,but the continuous working, the contraction effect is good.
- speed regulations scope broad, the movement is stable, may act according to contracts the request willfully to choose, stepless speed regulation.
- automatic warm controls, the precision teachers high, temperature hypothesis convenient, the demonstration is direct-viewing. the temperature may adjust the scope to be broad, adapts the diffrent material contraction request.
- use the hot blast circulation, the heat contracts the room temperature evenly , is stable.
- operations simple, control reliable, the compatibility is broad.

main technical parameter

Type	RPM-45o
Trasfer rate	0-10m/min
Max contraction size	450*280mm
Power source	380V, 50Hz
Ppower	16KW
Temperature control	0-300 centigrade
Machine net wight	200KG

[Easy inquiry this item !](#)

[Page Up](#)